

Wireless thermometer, hygrometer, barometer for external probe, Sigfox IoT

code: W7811



The wireless sensor measures temperature, humidity and pressure from external sensor on the cable (not included). It features a simple, compact design and is positioned directly in the measured area.

Measured values are displayed on the display and are regularly sent, in an adjustable time interval from 10 min to 24 h, by radio transmission in Sigfox to [COMET Cloud](#). After the emergence of a new alarm (or the extinction of an alarm in progress), an extraordinary alarm message is sent at the latest within 10 minutes.

The temperature and humidity probe is not included in delivery, probe of the appropriate length and design you can choose in optional accessories.

The wireless meter includes **Traceable calibration certificate** with declared metrological traceability of etalons is based on requirements of **EN ISO/IEC 17025 standard**.

Radio configuration zone RC1. More information about [Sigfox Radio Configurations \(RC\)](#).
[Check the Sigfox coverage in your region.](#)

Technical data

TEMPERATURE SENSOR	
Measuring range	according to the connected probe Digi/E
Accuracy	according to the connected probe Digi/E
Resolution	0.1 °C
Response time t90 of temperature measurement (temperature step 20°C, air flow approximately 1m/s)	according to the connected probe Digi/E
HUMIDITY SENSOR	
Measuring range	according to the connected probe Digi/E
Accuracy	according to the connected probe Digi/E
Resolution	0.1% RH
DEW POINT	
Measuring range	according to the connected probe Digi/E
Accuracy	according to the connected probe Digi/E
Resolution	according to the connected probe Digi/E
ATMOSPHERIC PRESSURE SENSOR SENSOR	
Measuring range	600 to 1100 hPa
Accuracy	±1.3 hPa at 23 °C from 800 to 1100 hPa
Resolution	0.1 hPa
GENERAL TECHNICAL DATA	
Operating temperature	-30 to +60 °C

Channels	internal atmospheric pressure sensor, 1x connectable temperature+humidity probe
Message transmission interval	adjustable 10 minutes, 20 minutes, 30 minutes,1 hour, 3 hours, 6 hours, 12 hours, 24 hours
Alarm message sending interval	10 minutes
Operating frequency	868 MHz
Maximum transmission power	25mW
Sigfox radiation class	0U
Radio configuration zone	RC1 (operation is possible in Europe, Iran, Oman and South Africa)
Typical range of transmitter	50 km in the field, 3 km in the city
Power	Lithium battery 3.6 V, AA size
Protection class	IP54
Dimensions	126 x 89 x 40mm
Weight (including batteries)	150g
Warranty	3 years